POSICHARGE™ MVS 800



High Output. Reliable. Intelligent Multi-Vehicle Charge

PosiCharge[™] systems bring you industry-leading fast charge solutions for airport ground support equipment, outdoor-rated to withstand extreme conditions.

MVS is our multiple-port, multi-vehicle fast charge system, especially designed to lower utility costs for distribution, warehousing, and general manufacturing. An MVS800 can charge up to 16 industrial vehicles (e.g. tow tugs, baggage tractors, belt loaders, etc.) at the same time. This cost saving alternative to conventional charging makes implementing and using electric GSE vehicles more cost effective. The more vehicles charged at once, the greater the cost benefit.

Like the DVS, MVS features the highest power quality and most diverse multi-voltage, multi-amperage flexibility of any fast charging system available today. MVS systems are installed all across the world's largest airports, as well as Fortune and Global 100 companies. And like all PosiCharge chargers, the MVS800 works with a broad range of battery voltages and has the same data management and onboard intelligence.



eGSE

KEY OPTIONS

CEC CERTIFICATION - Chargers meet CEC round trip efficiency and idle power standards required by certain states.

BATTERY RX[™] – Advanced battery monitor for maximum battery life with optional cellular connectivity and data services.

POSINET[™] – Works with cellular Battery Rx to collect battery charge data and run usage reports.

POWER SHARE - Allows you to share power with existing circuits and other devices at the jet bridge.



in 🗗 🗲 📟



posichargeprocore.com posicharge.com @posicharge


POSICHARGE™ MVS Multi-Vehicle System **ADVANTAGE**

- More charge power for heavy applications, compared to other multiple vehicle chargers
- Charge 3x the equipment with the same power » you were using for conventional chargers
- Lower infrastructure costs compared to large scale single-vehicle systems
- Lower maintenance & operational cost
- Flexible up to 16-vehicle charge option
- Requires no battery changing operations
- Designed to maximize available electrical » infrastructure, keep fleet operational 24/7 and extend battery life
- Euro and Burton Output Connector/Cable Options









SPECIFICATIONS

MODEL MVS800: POWERSERVER

POWER RATING	80kW
UTILITY REQUIREMENTS	480/600VAC, 3 PHASE
FULL LOAD AMP DRAW	100A / 80A
MAX CIRCUIT BREAKER RATING	125A / 100A
POWER FACTOR	0.96
EFFICIENCY	95%
WEIGHT	1,405 LBS
DIMENSIONS	62"H X 42"W X 27"D

POWFRSTATION

I ON ENOTION	
POWER RATING	60kW
BATTERY VOLTAGE RANGE	24V - 96V
MAX OUTPUT CURRENT (DUAL MODE)	250A
MAX OUTPUT CURRENT (SINGLE MODE)	500A
WEIGHT	304 LBS
DIMENSIONS	30"H X 30"W X 19"D
COMMUNICATION PORT	RS232

HIGHEST SAFETY STANDARDS: CE, UL1012, CSA

All specifications are subject to change, image shown is a representation; production model may vary slightly in appearance



PosiCharge™ systems, a product line of AeroVironment, Inc. 1.866.767.4242 | info@posicharge.com AeroVironment[™] © 2016 AeroVironment, Inc.

posichargeprocore.com posicharge.com

